

mAGE316U20-iSCSI

3U 16-bay iSCSI RAID Storage Rackmount JBOD Chassis



Features

- Aluminum Heat-Sink Body and Fan Coolers for Best Ventilation
- Supports Sixteen SATA Drives
- Individual Key Lock of Each HDD Tray for Physical Security
- LED Indicators for Power and Activity on Each HDD Tray
- Environmental Monitoring with Power/FAN/TEMP LEDs and Mutable Buzzer Alarm
- Front-end Dual Gigabit Ethernet TCP/IP Offload Device
- Hardware RAID Intel IOP 331 64-bit processor
- Supports Raid Levels 0, 1, 0+1, 5, 6, JBOD
- Online Volume Expansion & Migration
- Supports MPIO in Windows 2000 & Windows 2003 Server system
- Event notification via Email, SNMP trap, Windows & Browser

Specifications

Dimension (W x H x D)	19 x 5.16 x 18 inches
Cooling	Two 7.5 x 7.5 x 2.8 cm Blowers Fans
HDD Interface	SATA II (3Gbps)
Host Interface	Dual Port iSCSI Gigabit Ethernet
LED Display	Green – Power on indicator Blue – Busy (HDD Accessing) indicator
Hot-Swap	Both on Host and Device
Material	Heavy-duty Cold-rolled Steel
Packaging Information	Enclosure x 1 HDD Tray x 16 Power Cord x 1 Manual CD-ROM x 1 Hard Disk Drive Mounting Screw x 64 Key for HDD Tray x 2
Power Supply	400W single psu (Server-grade) (with 400W redundant psu model: mAge316U20-iSCSI-R)
RAID Level	0, 1, 0+1, 3, 5, 6 & JBOD
O.S. Support	OS Independent, Compatible with Windows, Linux & Mac
CPU & Memory	Intel IOP 331 & 512MB DDR



mAGE212U40-PCI-E

2U 12-bay PCI-Express Rackmount JBOD Chassis



Features

- Supports SAS/SATA (3Gbps)
- External 2U-12 Bay Rack-mount Chassis
- External PCI-e (PCI-Express) x8 Host Interface
- Backplane Design for up to 12 Removable SAS/SATA Drive Trays
- Dual Hot Swappable Power Supplies
- Individual key lock of each HDD tray for physical security
- LED indicators for power and activity on each HDD tray
- Environmental Monitoring with Power/FAN/TEMP LEDs and mutable buzzer alarm

Specifications

Dimension (W x H x D)	19 x 3.5 x 23.5 inches
Cooling	60mm Fan x 2
HDD Interface	SAS/SATA
Host Interface	PCI-e x 8
Data Transfer Rate	SAS/SATA 3 Gbps
LED Display	Green - Power on indicator Blue - Busy (HDD Accessing) indicator
Hot-Swap	Both on Host and Device
Material	Heavy-duty cold-rolled steel
Packaging Information	Enclosure x 1 HDD Tray x 12 PCI-e x 8 Adapter Card x 1 Power Cord x 1 Manual CD-ROM x 1 Hard Disk Drive mounting screw x 48 Key for HDD tray x 2
Power Supply	400W single psu (Server-grade) (with 400W redundant psu model: mAge212U40-PCI-E-R)
O.S. Support	OS Independent

Recommended Accessories

Model No.	Description
cAGE-AAM1MI-H	Internal mini SAS to 4 SATA Cable
cAGE-AAMMMI-H	Internal mini SAS to Internal mini SAS Cable